UNIVERSITY OF CAMBRIDGE INTERNATIONAL EXAMINATIONS GCE Ordinary Level

MARK SCHEME for the May/June 2011 question paper for the guidance of teachers

5054 PHYSICS

5054/32

Paper 3 (Practical Test), maximum raw mark 30

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

• Cambridge will not enter into discussions or correspondence in connection with these mark schemes.

Cambridge is publishing the mark schemes for the May/June 2011 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.



Page 2		ge 2	Mark Scheme: Teachers' version	Syllabus	Paper 32	
			GCE O LEVEL – May/June 2011	5054		
1	(a)	d in the	range 48.0 cm to 52.0 cm, recorded to the nearest mm	or better with unit.	B1	[1]
	(c)	Align PQ to vertical string to which mass is attached/align PQ with window frame or other vertical line in room/measure two horizontal distances from vertical half metre rule (checked with set square at bench).				[1]
	(d)	x should	be 0.9 cm to 1.1 cm less than <i>d</i> .		B1	
		-	measured to the nearest mm with unit seen in (i) or to 80.0 cm).	(ii) and y sensible	B1	[2]
	(e)	Correct	calculation of M with unit from sensible values of x and	y. (Ignore s.f.)	B1	[1]
				[Total: 5]		
2	(a)	<i>l</i> in rang	e 79.5 cm to 80.5 cm, recorded to the nearest mm with	unit.	B1	[1]
	(b)		peated or at least 40 oscillations timed and average va 7.3s.	ulue in range 34.5s	B1	[1]
			range 1.75 s to 1.85 s obtained from 20 <i>T</i> . it seen in (i) or (ii) else – 1)		B1	[1]
	(c)		calculation of g from sensible data giving a number i 900 to 1100.	n the range 9.0 to	M1	
		Correct unit (Ignore s.f.).		A1	[2]	
					[Total: 5]	
3	(a)	Correct	normal and angle of incidence = 60° by eye.		В1	[1]
	(b)	correct	of straight edge at M, lines drawn to represent the or construction inside block with angle of reflection in the rect unit and from correct diagram.		B1	
			P_2 labelled with one mark within 2.0 cm of the block a 0 cm of the line indicating the margin.	and the other mark	B1	[2]
	(c)	P ₃ and F	$ ho_4$ labelled on the incident ray and in approximately the	correct position.	B1	
		Angle of correct of	f incidence within the block found to be in the range diagram.	38° to 43° from a	B1	[2]
				[Tota	l: 5]	

Page 3	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE O LEVEL – May/June 2011	5054	32

4 Preliminary Results

(a)	Circuit diagram showing: power supply, LED (accept LED or diode symbol, ignore polarity), resistor (X), resistor or gap (between A and B), ammeter and voltmeter in parallel with LED. (ignore switch) (-1 for each error in the diagram)	B2	[2]			
(b)	V in the range 1.5 V to 2.5 V measured to 0.1 V or better with unit.	B1				
	$\it I$ in the range 5.0 mA to 25.0 mA measured to the nearest 0.1 mA or better with unit.	B1	[2]			
(c)	Correct calculation of power with unit consistent with I and V .	B1	[1]			
<u>Table</u>						
(d)	Table with units for resistance, <i>V, I,</i> and power.	B1				
	In awarding the next marks good results should be judged by checking that I decreases as R increases. Note that a straight line on the graph will not necessarily indicate good results.					
	3 good values for <i>I</i> .	B1				
	4 th good value for <i>I</i> .	B1				
	5 th & 6 th good values for <i>I</i> .	B1				
	$7^{ ext{th}}$ good value for I	B1	[5]			
<u>Graph</u>						
(e)	Axes labelled with units and correct orientation. (Allow e.c.f. from wrong unit in table but not no units)	B1				
	Suitable scale, not based on 3, 6, 7 etc. with data occupying more than half the page in both directions. (Allow the graph to start at the origin.)	B1				
	Two points plotted correctly – check the two points furthest from the line. This mark can only be scored if the scale is easy to follow. (Points must be within $\frac{1}{2}$ small square of the correct position)	B1				
	Best fit fine line and fine points or crosses. (Line thickness to be no greater than the thickest lines on the grid)	B1	[4]			
<u>Calculations</u>						
(f)	Value of power, correctly read off at 10 mA with unit.	B1	[1]			

[Total: 15]