UNIVERSITY OF CAMBRIDGE INTERNATIONAL EXAMINATIONS GCE Ordinary Level

MARK SCHEME for the October/November 2011 question paper for the guidance of teachers

5054 PHYSICS

5054/31

Paper 3 (Practical Test), maximum raw mark 30

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

Cambridge will not enter into discussions or correspondence in connection with these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2011 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.

	Page 2			Mark Scheme: Teachers' version	Syllabus	Paper 31	
				GCE O LEVEL – October/November 2011 5054			
1	Used set			ed the height of the string above the bench at 2 places/ t square to check angle MBC/ with horizontal surface in room, e.g. bench.		B1	[1]
	(c)) l in range 24.0 cm to 26.0 cm and $l > h_1 - h_2$ with correct unit seen somewhere.					
		All lengths recorded to the nearest mm or better.					
	(d)	Correct calculation of $\sin \theta$ and θ giving a value of θ in the range 40° to 80°.				C1	
	heta in the range 50° to 70° with unit.					A1	[2]
2	(a)	(ii)	•	ect value in range 12.0s to 16.0s, otherwise allow va Supervisor's value, with t_1 repeated and averaged. and.		B1	[1]
	((iii)	Corr	rect calculation of T_1 to 2/3 s.f. and unit seen somewhe	re in (a) .	B1	[1]
	(b)		(a) ar	ues of t_2 , T_2 found correctly and $T_2 > T_1$ with 2/3 s.f. and (b) , penalise significant figures once only and pen		B1	[1]
	(c)	(Allo	ow 0.	calculation of ratio of periods with value in the range 1. 67 to 0.90 if f calculated in (a) and (b) .) ow t_2/t_1 .)	10 to 1.50.	M1	
		Rati	io in r	range 1.20 to 1.40 with no unit (or 0.71 to 0.83 if <i>f</i> used	l).	A1	[2]
					[Tota	l: 5]	
3	(h)	u in					
J	(5)	<i>u</i> in the range 16.0 cm to 21.0 cm and $u + v = 100.0 \pm 1.0$ cm. Ignore precision and unit. At least one measurements recorded to the nearest mm or $\frac{1}{2}$ mm with unit.				M1 A1	[2]
	(c)	(i)	13.0	und correctly from more than one gap and in the range of the multiple of the gap, but multiple of the gap and the gap a		B1	[1]
		(ii)		inimum of 3 spacings used to find <i>d</i> . This may be show ated in the results.	vn on a diagram	B1	[1]
	(d)		the in (c)(i	range 1.3mm to 3.0mm from correct calculation, with i).	unit seen here	B1	[1]
						[Total: 5]	

Page 3	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE O LEVEL – October/November 2011	5054	31

4 Preliminary Results

(a)	Circuit diagram showing: Series circuit with power supply (allow d.c or a.c), two resistors, (switch) and						
	ammeter.	B1					
	Voltmeter in parallel with power supply and one resistor. Voltmeter in series loses both marks.	B1	[2]				
(b)	V in the range 0.7V to 1.7V measured to 0.1V or better with unit. I in the range 0.050A to 0.110A measured to the nearest 0.01A or better with						
	unit.	B1	[2]				
<u>Table</u>							
(c)	Table with units for resistance, <i>V</i> and <i>I</i> .	B1					
	Minimum of 3 readings for V with correct trend for all readings i.e. as R increases V increases.	M1					
	Minimum of 3 readings for I with correct trend for all readings i.e. as R increases I decreases.	M1					
	7 values in total.	A1	[4]				
Gra	nph						
	Axes labelled with units and correct orientation. (Allow e.c.f. from wrong unit in table but not no units)	B1					
	Suitable scale, not based on 3, 6, 7 etc. with data occupying more than half the page in both directions.	B1					
	Two points plotted correctly – check the two points furthest from the line. This mark can only be scored if the scale is easy to follow. (Points must be within ½ small square of the correct position)	B1					
	Best fit fine line and fine points or crosses. (Line thickness to be no greater than the thickest lines on the grid)	B1	[4]				
<u>Calculations</u>							
(e)	Use of a triangle that occupies more than half the drawn line. (Not using points that are not on the line or points that are on a curve.)	B1					
	Correct calculation 2/3 s.f. (ignore absence of unit).	B1					
	Gradient in range 26 to 40 (Ω or V/A) from correct calculation with consistent sign (expect negative sign). (Allow –0.026 to –0.040 if I axis in mA.)	B1	[3]				