MARK SCHEME for the May/June 2012 question paper

for the guidance of teachers

9702 PHYSICS

9702/33

Paper 3 (Advanced Practical Skills 1), maximum raw mark 40

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

• Cambridge will not enter into discussions or correspondence in connection with these mark schemes.

Cambridge is publishing the mark schemes for the May/June 2012 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.



	Page	e 2	Mark Scheme: Teachers' version	Syllabus	Paper
			GCE AS/A LEVEL – May/June 2012	9702	33
1	(a) (i	i) \	/alue of h_0 in range 0.70 m > h_0 > 0.50 m. Consistent with ur	nit.	[1]
	(b) (ii	i) \	/alue of <i>h,</i> less than <i>h</i> ₀ in (a)(ii) , with unit.		[1]
	(c) F N	⁻ive ∕Iajo	sets of readings of <i>h</i> and <i>m</i> scores 5 marks, four sets scor r help from Supervisor –2 (setting up apparatus). Minor he	es 4 marks etc. Ip from Supervis	sor –1. [5]
	F	Rang To in	je of <i>m</i> : clude 0.350 kg.		[1]
	C E T (/	Colui Each The <i>h</i> ₀ –	mn headings: column heading must contain a quantity and a unit. unit must conform to accepted scientific convention e. <i>h)/m</i> / m kg ⁻¹ , 1/m / kg ⁻¹	g. <i>m /</i> kg, <i>m</i> (kg	[1]) or <i>m</i> in kg,
	C A	Cons All va	istency: Ilues of <i>h</i> must be given to the nearest mm.		[1]
	S S Ir	Signi Signi n the	ficant figures: ficant figures for every row of values of 1/ <i>m</i> same as or or a table.	ne greater than	[1] <i>m</i> as recorded
	C V	Calcu /alue	ulation: es of $(h_0 - h)$ /m calculated correctly.		[1]
	(d) ((i) A S S	Axes: Sensible scales must be used, no awkward scales (e.g. 3: Scales must be chosen so that the plotted points occupy both x and y directions. Scales must be labelled with the quantity that is being plott	I0). at least half the	[1] e graph grid in
		F A C V	Scale markings must be no more than 3 large squares apa Plotting of points: All observations in the table must be plotted. Diameter of plots must be \leq half a small square (no 'blobs') Nork to an accuracy of half a small square.).	[1]
		C A F	Quality: All points in the table must be plotted (at least 4) for this n points must be less than 0.5 kg ⁻¹ (0.0005 g ⁻¹) of 1/ <i>m</i> of a s	nark to be award traight line.	[1] ded. Scatter of
	(i	ii) L T A L	Line of best fit: Judge by balance of all points on the grid about the candid There must be an even distribution of points either side of t Allow one anomalous point only if clearly indicated by the o Line must not be kinked or thicker than half a small square	ate's line (at lea the line along the candidate.	[1] st 4 points). e full length.
	(ii	ii) (T E	Gradient: The hypotenuse of the triangle must be at least half the len Both read-offs must be accurate to half a small square in b Do not allow $\Delta x / \Delta y$.	gth of the drawr oth <i>x</i> and <i>y</i> direo	[1] n line. ctions.

Page 3			Mark Scheme: Teachers' version	Syllabus	Paper
			GCE AS/A LEVEL – May/June 2012	9702	33
		y-int Eithe Che Rea Or:	ercept: er: ck correct read off from a point on the line and substitu d off must be accurate to half a small square in both <i>x</i>	ited into $y = mx + and y$ directions.	[1] - <i>c.</i>
		Cne	ck read-off of the intercept directly from the graph.		
	(e) Va	lue of	P = candidate's gradient. Value of Q = candidate's inte	ercept.	[1]
	Un	it for F	P (e.g. m) consistent with value, and Q (m kg^{-1})		[1]
					[Total: 20]
2	(b) (ii)	Valu	ie of $ heta_0$ to the nearest degree or 0.5° in range 70° # $ heta$ #	∉ 80°	[1]
	(iii)	Valu	le of $ heta$ with unit, $ heta < heta_0$		[1]
	(iv)	Corr	ect calculation of $(\theta_0 - \theta)$		[1]
	(c) (i)	Valu	e of raw <i>d</i> with unit to nearest mm.		[1]
	(ii)	Abso If re rang	olute uncertainty in 2 mm < <i>d</i> < 5 mm. peated readings have been taken, then the absolut le. Correct method shown to find the percentage uncer	e uncertainty ca tainty.	[1] n be half the
	 (d) Second value of θ₀ within 1 °C of first value of θ₀. Second value of θ. Second value of Δθ > first value of Δθ (check second value of d > first value experimentation of the second value of d > first value of Δθ (check second value of d > first value experimentation). 		I > first value of α	[1] [1] 1). [1] [1]	
	(e) (i)	Two	values of <i>k</i> calculated correctly.		[1]
	(ii)	Just	ification of s.f. in <i>k</i> linked to <u>significant figures</u> in <i>d</i> and	$\Delta \theta$.	[1]
	(iii)	Sen: spec	sible comment relating to the calculated values of cified by the candidate.	k, testing agair	nst a criterion [1]

Page 4	Page 4 Mark Scheme: Teachers' version		Paper
	GCE AS/A LEVEL – May/June 2012	9702	33

(f)

	(i) Limitations 4 max.	(ii) Improvements 4 max.	No credit/not enough
A	two results not enough	take more readings <u>and plot a graph/</u> calculate more <i>k</i> values and <u>compare</u>	'repeat readings' on its own/ few readings/ take more readings and (calculate) average <i>k</i> / only one reading
В	heat lost <u>through sides and /or</u> <u>bottom</u>	method to reduce heat loss/ lag/ insulate/ polystyrene container	use of lid/ heat loss in warming bowl/cup/ draughts/ heat loss to surroundings
С	temperature change is small/ $\Delta \theta$ values too close	time for longer/ higher starting temperature/ greater range of surface areas	
D	large (percentage) uncertainty in $\Delta \theta$	use thermometer with greater sensitivity or precision/ use thermometer that can read to 0.1 °C	use more accurate thermometer/ thermometer not precise enough/ not just 'digital thermometer'
E	water in bowl barely covers (bulb of) thermometer	use larger volume of water/ use of thermocouple/ other <u>small</u> temperature <u>sensor</u> (e.g. probe)	not just 'digital thermometer' any reference to stirrer/ non-uniform temperature/ thermometer touching base
F	parallax error in measuring <u>d</u> / reason for difficulty in access in measuring <u>d</u>	use dividers/calipers	string measurements to measure <i>d</i>
G	difficult to mark level with reason	method of making mark stay e.g. depth gauge/ calibrated marks/ marker on outside	

Do not allow: use of coloured ink/reaction time/fans/draughts/water left behind/beakers not accurate/ helpers.

[Total: 20]