MARK SCHEME for the October/November 2015 series

9709 MATHEMATICS

9709/41

Paper 4, maximum raw mark 50

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2015 series for most Cambridge IGCSE[®], Cambridge International A and AS Level components and some Cambridge O Level components.

® IGCSE is the registered trademark of Cambridge International Examinations.



Page 2	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2015	9709	41

Mark Scheme Notes

Marks are of the following three types:

- M Method mark, awarded for a valid method applied to the problem. Method marks are not lost for numerical errors, algebraic slips or errors in units. However, it is not usually sufficient for a candidate just to indicate an intention of using some method or just to quote a formula; the formula or idea must be applied to the specific problem in hand, e.g. by substituting the relevant quantities into the formula. Correct application of a formula without the formula being quoted obviously earns the M mark and in some cases an M mark can be implied from a correct answer.
- A Accuracy mark, awarded for a correct answer or intermediate step correctly obtained. Accuracy marks cannot be given unless the associated method mark is earned (or implied).
- B Mark for a correct result or statement independent of method marks.
- When a part of a question has two or more "method" steps, the M marks are generally
 independent unless the scheme specifically says otherwise; and similarly when there are
 several B marks allocated. The notation DM or DB (or dep*) is used to indicate that a
 particular M or B mark is dependent on an earlier M or B (asterisked) mark in the scheme.
 When two or more steps are run together by the candidate, the earlier marks are implied and
 full credit is given.
- The symbol [↓] implies that the A or B mark indicated is allowed for work correctly following on from previously incorrect results. Otherwise, A or B marks are given for correct work only. A and B marks are not given for fortuitously "correct" answers or results obtained from incorrect working.
- Note: B2 or A2 means that the candidate can earn 2 or 0. B2/1/0 means that the candidate can earn anything from 0 to 2.

The marks indicated in the scheme may not be subdivided. If there is genuine doubt whether a candidate has earned a mark, allow the candidate the benefit of the doubt. Unless otherwise indicated, marks once gained cannot subsequently be lost, e.g. wrong working following a correct form of answer is ignored.

- Wrong or missing units in an answer should not lead to the loss of a mark unless the scheme specifically indicates otherwise.
- For a numerical answer, allow the A or B mark if a value is obtained which is correct to 3 s.f., or which would be correct to 3 s.f. if rounded (1 d.p. in the case of an angle). As stated above, an A or B mark is not given if a correct numerical answer arises fortuitously from incorrect working. For Mechanics questions, allow A or B marks for correct answers which arise from taking *g* equal to 9.8 or 9.81 instead of 10.

Page 3	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2015	9709	41

The following abbreviations may be used in a mark scheme or used on the scripts:

AEF	Any Equivalent Form (of answer is equally acceptable)
AG	Answer Given on the question paper (so extra checking is needed to ensure that the detailed working leading to the result is valid)
BOD	Benefit of Doubt (allowed when the validity of a solution may not be absolutely clear)
CAO	Correct Answer Only (emphasising that no "follow through" from a previous error is allowed)
CWO	Correct Working Only – often written by a 'fortuitous' answer
ISW	Ignore Subsequent Working
MR	Misread
MR PA	Misread Premature Approximation (resulting in basically correct work that is insufficiently accurate)
	Premature Approximation (resulting in basically correct work that is insufficiently

Penalties

- MR –1 A penalty of MR –1 is deducted from A or B marks when the data of a question or part question are genuinely misread and the object and difficulty of the question remain unaltered. In this case all A and B marks then become "follow through √" marks. MR is not applied when the candidate misreads his own figures this is regarded as an error in accuracy. An MR –2 penalty may be applied in particular cases if agreed at the coordination meeting.
- PA –1 This is deducted from A or B marks in the case of premature approximation. The PA –1 penalty is usually discussed at the meeting.

F	Page		Scheme		Syllabus Pa					
		Cambridge International AS/A I	Level – Oc	tober/l	November 2015 9709 4	1				
1	(i)	$200g \times 0.7$	M1		For using WD = $mg \times h$					
		Work done = 1400 J	A1	2						
	(ii)	1400/1.2	M1		For using Power = WD/Time					
		Average Power = 1170 W	A1√ [^]	2						
2	(i)	$a = g \sin 30 = 5$	B1							
		2.5 = 0 + 5t	M1		Using $v = u + at$					
		t = 0.5 Time = 0.5 s	A1	3						
	(ii)	$v^2 = 0 + 2 \times 5 \times 3 = 30$	B1							
		$-1 = 0.5a \rightarrow a = -2$			For applying Newton's second law t particle and using	to the				
		$0 = 30 + 2 \times (-2) \times s$	M1		$v^2 = u^2 + 2as$					
		Distance = $7.5 \mathrm{m}$	A1	3						
		First alternative method for 2(ii)								
		$v^2 = 0 + 2 \times 5 \times 3 = 30$	B1							
		$0.5 \times 0.5 \times 30 = 1 \times \text{distance}$	M1		KE lost = WD against Friction					
		Distance = 7.5 m	A1	3						
		Second alternative method for 2(ii)								
		$PE lost = 0.5 \times 10 \times 3 sin 30 = 7.5$	B1		Using PE lost = <i>mgh</i>					
		$7.5 = 1 \times \text{distance}$	M1		PE lost = WD against Friction					
		Distance = $7.5 \mathrm{m}$	A1	3						
3	(i)		M1		For applying Newton's second law t lorry up the hill	to the				
		$F - 24000g \sin 3 - 3200 = 24000 \times (0.2)$	A1		[<i>F</i> = 20561]					
		$Power = F_V = 20561 \times 25$	M1		Using $P = Fv$					
		Power = $514 \mathrm{kW}$	A1	4						
	(ii)	$DF = 3200 + 24000g \sin 3$ [=15761]	M1		Using Newton's second law up the h the steady case	nill in				
		$v = 500000 / 15761 = 31.7 \mathrm{ms}^{-1}$	A1	2	P = Fv so $v = P/F$					

Page			tobor/	November 2015	Syllabus 9709	Paper		
	Cambridge International AS/A Le	vei – Od		November 2015	9709	41		
4	$F = 0.2 \times mg \cos 35$	B 1		Maximum value				
		M1		 For resolving forces along the plane in either case Equilibrium, on the point of moving up the plane Equilibrium, on the point of moving down the plane For solving either 				
	$5g - mg\sin 35 - 0.2 mg\cos 35$ $= 0$	A1						
	$5g - Mg \sin 35 + 0.2 Mg \cos 35$ = 0	A1						
	m = 6.78 or $M = 12.2$	M1						
	6.78 ≤ mass ≤ 12.2	A1	6					
5 (i)		M1		For resolving forces either horizontally overtically				
	$F\cos 70 + 20 - 10\cos 30$ = $R\cos 15$	A1						
	$10\sin 30 - F\sin 70 = R\sin 15$	A1						
		M1		For solving simul	For solving simultaneously			
	F = 1.90 N and $R = 12.4 N$	A1	5					
	Alter	Alternative method for 5(i)						
	[X = 0.342 F + 11.34 Y = 0.94 F - 5]	M1		For finding comp the <i>x</i> and <i>y</i> direct	Finding components of the forces in x and y directions			
	$(0.342 F + 11.34)^{2} + (0.94 F - 5)^{2}$ $= R^{2}$	A1						
	$\tan 15 = (5 - 0.94F) / (0.342F + 11.34)$	A1						
		M1		Solve the tan 15 equation for F and substitute to find R				
	F = 1.90 N and $R = 12.4$ N	A1	5					
(ii)	$11.7^2 = 0 + 2a \times 3$							
	<i>a</i> = 22.815	B 1						
	$R\cos 15 = m \times 22.815$	M1		Applying Newtor particle in direction		v to the		
	Mass of bead = 0.526 kg	A1	3					

Page						Paper
	Cambridge International AS/A Level – October/November 2015					41
6 (i)	$s = 0.3t^2 - 0.01t^3$	M1		For integration		
	$s(5) = 0.3 \times 5^2 - 0.01 \times 5^3 = 6.25$	A1				
	a = 0.6 - 0.06t	M1		For differentiation	1	
	$a(5) = 0.6 - 0.0 \times 5 = 0.3 \text{ ms}^{-2}$	A1	4			
(ii)	Maximum velocity is when $0.6 - 0.06t = 0$	M1		For setting $a = 0$		
	[<i>t</i> = 10]	M1		For solving $a = 0$		
	Max velocity = 3 ms^{-1}	A1				
	$0.6t - 0.03t^2 = 1.5$			Setting velocity = half its maximum and attempting to solve a three term quadrati		
	$[t^2 - 20t + 50 = 0]$	M1			e a tillee terr	n quadratic
	Times are 2.93 s	A1				
	and 17.07 s	A1	6			

Page					Syllabus	Paper
Cambridge International AS/A Level – October/Novembe				lovember 2015	9709	41
7 (i)	$36 = 0 + 0.5 \times 0.5t^2$					
	$t = 12$ $v^2 = 0 + 2 \times 0.5 \times 36$	B1				
	<i>v</i> = 6	B1				
	$s = 6 \times 25$					
	remaining distance = $210 - 36 - 150 = 24$	B1				
	$24 = (6+0)/2 \times t$	M1		Using $s = (u + v)t/t$	2	
	<i>t</i> = 8					
	Total Time = $12 + 25 + 8 = 45$ s	A1	5			
(ii)	Distance travelled by cyclist = $36 + 6(t - 12)$	M1		For attempting dist cyclist for $t > 12$	ance travell	ed by
	Distance travelled by car = $0.5 \times 4 \times (t - 24)^2$	M1		For attempting dist	ance travell	ed by car
	$2t^2 - 96t + 1152 = 36 + 6t - 72$			Equating expressio solve a three term of		* -
	$[t^2 - 51t + 594 = 0]$	M1				
	t = 33 or t = 18	A1				
	Time = 33 s	B1	5	Choosing the corre	ect solution	